

LOGWOOD

SAFETY SHOES

Ref. LOG - Size: 38 to 47

EN ISO 20345: 2011 S3 WR CI HRO SRC

EN ISO 17249: 2013 Class 3 (28m/s)



The PPE Specialist

PRODUCT PHOTOS



UNISEX MODEL



DESCRIPTION

The Logwood is a class 3 (28m/s) chainsaw safety shoe featuring a Vibram® brand sole, eVent® waterproof-breathable inner lining and Perwanger® leather uppers. Very practical and safe the toe block allows the shoe to be opened while maintaining good foot support. Robust, they feature a rubber side stone guard.

3 MAIN BENEFITS

- **Vibram®**: These soles are made of an advanced rubber offering **unrivalled grip**, waterproofing and **optimum comfort**.
- **eVent®**: This **waterproof** membrane resists moisture and water molecules thanks to a direct ventilation system. Moisture wicks away from the fabric and prevents water from penetrating inside. This material helps users **stay dry** and **comfortable** when wearing it.

- **Perwanger®**: This **water-repellent leather** prevents water from seeping in, while ensuring the leather's **breathability**. Due to special tanning techniques this leather **resists abrasions** even on rocky terrain and **ensures longevity**.

WEIGHTS & DIMENSIONS

Size: 43

Weight: 1.28 kg

Height: 19 cm

PACKAGING

Packaged in packages of 3. Individually packaged. Logwood's packaging is made of cardboard with standardization **CITEO**.

Diagrams assemblent une nouvelle vie à nos produits.

VARIANT

Available in clay color «Bombay Brown»
Reference: **LOGN**



LOGWOOD

Ref. LOG - Size: 38 to 47

SAFETY SHOES

For resellers,
order on B2B



EN ISO 20345: 2011 S3 WR CI HRO SRC

EN ISO 17249: 2013 Class 3 (28m/s)

TECHNICAL SPECS



Elastic edging

Double-riveted
lacing hooks

Class 3, 28 m/s

Event® Direct Venting™
membrane sock lining

Flat D-eyelets

Ball-bearing grommets

Heel counter

Reflective strips

Lug shoe addition of studs

Bi-density midsole

Anti-slip Vibram® sole,
resistant to 300°C, oils and hydrocarbons

Perwanger® 2.8 - 3.0 mm
water-repellent cowhide
upper and gusset

Edge blocking
middle shoe

Extra-Large
Aluminum Protective Shell

Rubber stone
guards

Antifungal and
antibacterial primer

Composite
anti-perforation sole

STANDARD EN ISO 20345: 2011



200 J toe cap: forefoot protection against impact and crushing



Antistatic



**Heel shock
absorption**



Oil-hydrocarbon sole resistance



Anti-puncture insert 1100 N:
foot protection against perforation



Cold insulation



**300°C resistant
sole**



**Resistance of entire shoe to water
penetration and absorption. Waterproof
standards.**




Non-slip tread on detergent-and-watercoated
ceramic and glycerine-coated steel floors

STANDARD EN ISO 17249: 2013

Standard chainsaw protection class 3 (28 m/s)

EN 17249



Class 3

COMPLIANCE



037214703/OI
Issued by a notified body 0498



SOLIDUR SAS

335, Impasse Teractive Ouest - ZA Teractive - 50140 Romagny-Fontenay, FRANCE

Tel. +33 (0)2 33 59 45 12

www.solidur.fr @solidurfrance

